

Nachfolgetyp für Artikel Nr.:173Z8103

Bitte prüfen Sie die An- bzw. Einbaumöglichkeit anhand des beigefügten Maßbildes.

Bauer Article No.: 189P0642

Helical geared torque motor

Type	: BG06-11/DWU06LA8/SP		
Starting torque	(Nm) : 3,75	Mounting	: B7
Synchron speed at shaft	(rpm) : 79	Terminal box position	: IV / A
Corrosion protection	: Standard	Dimensional drawing	: BG06
Painting	: RAL 7031	Catalogue	: DG 07
		net weight per unit	: approximately 9,5 kg
Add./Special design:	Suitable for ambient temperatures from -40 to 40°C.		

Gear design:

Type	: BG06 2 -staged Helical gear
Design code 11	: foot with clearance hole on side bottom
	: solid output shaft on gear side front (d: 17 mm)
Total gear reduction i	: 9,38
Add./Special design:	Lubricant type: PGLP 68

Design of the motor:

Type	: Three-phase squirrel cage torque motor DWU06LA8		
Voltage	(V) : 230/400	Speed	(rpm) : 750 synchron
Connection	: D/Y	IP prot. type per EN 60529	: IP 65
Frequency	(Hz) : 50	IC cool. type EN 60034-6	: IC 410
Starting current	(A) : 0,33/0,19	Design acc. to DIN VDE 0530-1/EN 60034-1	
Power factor (cos phi A)	: 0,76	Terminal box size	: KAG2
Temperature class	: F		
permissible blocking time (stoppage) under full voltage	(min): ongoing		
Add./Special design:	With Motor bearing grease Klüber Petamo GHY 133		

Please note:

Motor

Motor connection by means of CAGE-CLAMP.
CAGE CLAMP is a Registered Trademark of the company WAGO

Motor not within the scope of Regulation (EU) 2019/1781 according to Article2, paragraph 1a)(iv).