

B-Series B5

Gigabit Ethernet Stackable Edge Switch



Future-proofed with 802.3at
high-power PoE support

Automatic discovery and deployment
of VoIP services

High-availability stacking assures
reliable network operations

Automated management features
reduce operational costs

Investment protection via
comprehensive lifetime warranty

1.47 Tbps capacity and 809.5 Mpps

Product Overview

The Enterasys B5 is a scalable, high-performance Gigabit Ethernet switch that provides support for the bandwidth-intensive and latency-sensitive requirements of today's demanding business applications. The B5 is an excellent choice for environments that require complete multi-layer switching capabilities and support for high density 10/100/1000 Ethernet ports, cost effective 10GE uplinks, and basic routing and policy-based automation capabilities for advanced edge deployments.

The B5 incorporates the new 802.3at high-power PoE on all ports, translating into increased power provisioning for power-hungry devices such as Pan/Tilt/Zoom (PTZ) IP surveillance cameras, IP videophones, third party 802.11n access points and virtual desktops. Built-in high-power PoE support is a cost effective alternative for customers in place of purchasing separate PoE midspans, which can take away valuable rack space, add cost and contribute more cabling to the wiring closet.

The B5 provides high port density in a 1U footprint and is environmentally friendly by design. The B5's overall energy efficiency is further enhanced by a low current draw and an extreme tolerance for high environmental temperatures. A highly-scalable architecture and a comprehensive lifetime warranty ensure that a B5 network investment will sustain a secure, feature-rich and cost-effective network well into the future.

The B5's highly customizable Layer 2/3/4 packet classification capabilities work together with the 8 hardware-based priority queues associated with each Ethernet port to support a suite of differentiated services with as many as 8 distinct priority levels to provide guaranteed Quality of Service (QoS) for critical voice and video network traffic. In conjunction with its non-blocking L2 switching and L3 routing architecture, the B5's intelligent queuing mechanisms ensure that mission-critical applications receive prioritized access to network resources.

Benefits

Business Alignment

- Aligns network resource utilization with business goals and priorities
- Reliable network operation for mission-critical applications

Operational Efficiency

- Management automation capabilities reduce network operational expenses
- Automatic discovery and deployment of VoIP services

Security

- Ability to audit network for adherence to compliance regulations, such as PCI or HIPAA
- Network resources securely allocated according to user roles
- Network security maintained concurrently with user mobility

Support and Service

- Industry-leading customer satisfaction and first call resolution rates
- Personalized services, including site surveys, network design, installation, and training
- Comprehensive lifetime warranty, including feature upgrades and more

**There is nothing more important
than our customers.**

Reliability and Availability

The B5 design incorporates redundancy and failure protection mechanisms complete with automatic failover and recovery capabilities to provide a reliable network. An integral power supply is the primary source of power for the B5 and complete power redundancy is provided by an optional external power supply. A virtual switch can be created by interconnecting as many as eight B5s in a single stack, which can be managed via a single IP address with redundant management connections. The B5's closed-loop stacking capability utilizes bi-directional switch interconnects to maintain connectivity within the virtual switch despite any physical failures, which includes switches, cables and connections. Up to eight Ethernet ports can be grouped together to create a multi-link aggregation group (LAG). A LAG's Ethernet ports can be co-located on a single B5 or they can be distributed across multiple B5s within a stack to prevent a switch-level failure from disrupting data communications.

Advanced Quality of Service

Robust Quality of Service (QoS) features enable strong support for integrated multimedia networks, as well as all types of data-intensive applications. The B5 is a standards-based solution optimized for multimedia applications, including VoIP, videoconferencing and real-time collaboration. The B5 uses multiple standards-based discovery methods with Enterasys policy capabilities to automatically identify and provision VoIP services for IP phones from all major vendors. B5 switches provide dynamic mobility for VoIP clients to reduce operating costs; when an IP phone moves and plugs in elsewhere in the enterprise network, its VoIP service provisioning, security and traffic priority settings move with it, with no manual administration required.

Security

The B5 enables strong network security by utilizing its authentication and security features, which can be applied at the port level or at the user level. Making use of the Enterasys Network Management Suite's Policy Manager or a standard CLI, the Enterasys role-based architecture enables a network administrator to define distinct roles or profiles that represent operational groups within a business (e.g., employee, executive, guest, etc). Multiple users/devices per port can be authenticated via IEEE 802.1X, MAC address, or web authentication, and then assigned a pre-defined operational role.

Administrators can easily transition from RFC 3580 and complex access control list (ACL) deployments to the Enterasys role-based policy framework in a seamless fashion, without the need to make changes to their RADIUS infrastructure (e.g., adding filter-ID). In addition, the B5 also supports ACLs for supplementary network security. Network operations can be easily tailored to meet business-oriented requirements by providing each role with individualized access to network services and applications (e.g., a guest should have different network access privileges than an employee).

The B5 allows administrators even more network visibility, with the ability to audit their network for adherence to compliance regulations, such as PCI or HIPAA. The B5 is able to segment roles down to group levels, such as supporting a guest access role, helping to protect corporate applications and information.

Investment Protection

The B5 is a cost-effective, feature-rich, stackable switch that provides a broad set of features today and will continue to deliver benefits well into the future. All B-Series products include a lifetime warranty that includes warranty and support services for which many competitors charge additional fees – adding up to 10% of initial deployment costs on an annual basis. Included benefits, such as advanced hardware return, firmware feature upgrades (which most vendors cover at most for 90 days) and telephone support (which most don't include or severely limit) combine to significantly decrease operational costs for customers over the life of their network. For more information regarding warranty terms and conditions please go to <http://www.enterasys.com/support/warranty.aspx>.

Performance & Scalability

The B5, with support for 16,000 MAC addresses, provides scalable, wire-rate performance in support of the bandwidth-intensive and delay-sensitive requirements of today's demanding applications. Along with a switch capacity of 184 Gbps, the B5 provides up to 48 10/100/1000 Ethernet ports as well as two 10 GE ports. Leveraging the B5's stacking capability, as many as 8 B5s (both 24-port and 48-port combinations) can be interconnected in a single stack to create a virtual switch that provides 1.47 Tbps of capacity and up to 384 10/100/1000 Ethernet ports as well as 16 10GE uplink ports.

Features / Standards and Protocols

MAC Address Table Size

16,000

VLANs

4,096 VLAN IDs

1,024 VLAN Entries per Stack

Embedded Services

Ingress Rate Limiting

IP TOS Rewrite

Layer 2/3/4 Classification

Multi-layer Packet Processing

Switching Services

IEEE 802.1AB – LLDP

ANSI/TIA-1057 – LLDP-MED

IEEE 802.1D – MAC Bridges

IEEE 802.1s – Multiple Spanning Trees

IEEE 802.1t – 802.1D Maintenance

IEEE 802.1w – Rapid Spanning Tree

Reconvergence

IEEE 802.3 – Ethernet

IEEE 802.3ab – GE over Twisted Pair

IEEE 802.3ad – Link Aggregation

IEEE 802.3ae – 10 Gigabit Ethernet (fiber)

IEEE 802.3af – PoE

IEEE 802.3at – High Power PoE

(up to 30W per port)

IEEE 802.3i – 10Base-T

IEEE 802.3u – 100Base-T, 100Base-FX

IEEE 802.3z – GE over Fiber

Full/half duplex auto-sense support on all ports

IGMP Snooping v1/v2/v3

Jumbo Frame support (9,216 bytes)

Loop Protection

One-to-One and Many-to-One Port Mirroring

Port Description

Protected Ports

Host Protect – Broadcast/ Multicast/ Unknown

Unicast Suppression

Spanning Tree Backup Root

STP Pass-Thru

VLAN Support

Generic Attribute Registration Protocol (GARP)

Generic VLAN Registration Protocol (GVRP)

IEEE 802.1p – Traffic classification

IEEE 802.1q – VLAN Tagging

Protocol-based VLANs with Enterasys Policy

IEEE 802.3ac – VLAN Tagging Extensions

Port-based VLAN (private port/private VLAN)

Tagged-based VLAN

VLAN Marking of Mirror Traffic

Quality of Service

8 Priority Queues per Port

802.3x Flow Control

Class of Service (CoS)

IP Precedence

IP Protocol

Queuing Control – Strict and

Weighted Round Robin

Source/Destination IP Address

Source/Destination MAC Address

Security

ARP Spoof Protection

DHCP Spoof Protection

Dynamic and Static MAC Locking

EAP Pass Thru

Hybrid Mode

IEEE 802.1X Port Authentication

MAC-based Port Authentication

RADIUS Accounting for network access

RADIUS Client

RFC 3580 – IEEE 802.1X RADIUS Usage

Guidelines

Multi-user Authentication

Password Encryption

Secure Networks Policy

Secured Shell (SSHv2)

Secured Socket Layer (SSL)

User and IP Phone Authentication

Web-based Port Authentication

IPv4 Routing

Standard Access Control List (ACLs)

Extended ACLs

VLAN-based ACLs

ARP & ARP Redirect

IP Helper Address

RFC 826 – Ethernet ARP

RFC 1058 – RIP v1

RFC 1256 – ICMP Router Discovery Messages

RFC 1724 – RIPv2 MIB Extension

RFC 2236 – IGMPv2

RFC 2453 – RIP v2

RFC 3046 – DHCP/BootP Relay

Static Routes

MIB Support

Enterasys Entity MIB

Enterasys Policy MIB

Enterasys VLAN Authorization MIB

ANSI/TIA-1057 – LLDP-MED MIB

IEEE 802.1AB – LLDP MIB

IEEE 802.1X MIB – Port Access

IEEE 802.3ad MIB – LAG MIB

RFC 826 – ARP and ARP Redirect

RFC 951, RFC 1542 – DHCP/BOOTP Relay

RFC 1213 – MIB/MIB II

RFC 1493 – BRIDGE-MIB

RFC 1643 – Ethernet-like MIB

RFC 2096 – IP Forwarding Table MIB

RFC 2131, RFC 3046 – DHCP Client/Relay

RFC 2233 – IF-MIB

RFC 2271 – SNMP Framework MIB

RFC 2618 – RADIUS Authentication

Client MIB

RFC 2620 – RADIUS Accounting Client MIB

RFC 2668 – Managed Object Definitions for

802.3 MAUs

RFC 2674 – P-BRIDGE-MIB

RFC 2674 – QBRIDGE-MIB VLAN

Bridge MIB

RFC 2737 – Entity MIB (physical branch only)

RFC 2819 – RMON-MIB

RFC 2933 – IGMP MIB

RFC 3413 – SNMP v3 Applications MIB

RFC 3414 – SNMP v3 User-based Security

Module (USM) MIB

RFC 3415 – View-based Access Control

Model for SNMP

RFC 3584 – SNMP Community MIB

RFC 3621 – Power over Ethernet MIB

Management

Alias Port Naming Command Line

Interface (CLI)

Configuration Upload/Download

Editable Text-based Configuration File

TFTP Client

Multi-configuration File Support

NMS Automated Security Manager

NMS Console

NMS Inventory Manager

NMS Policy Manager

Node/Alias Table

RFC 768 – UDP

RFC 783 – TFTP

RFC 791 – IP

RFC 792 – ICMP

RFC 793 – TCP

RFC 826 – ARP

RFC 854 – Telnet

RFC 951 – BootP

RFC 1157 – SNMP

RFC 1901 – Community-based SNMPv2

RFC 2933 – IGMP MIB

RFC 3176 – sFlow

RFC 3413 – SNMP Applications MIB

RFC 3414 – SNMP User-based Security

Module (USM) MIB

RFC 3415 – View-based Access Control

Model for SNMP

RFC 3826 – Advanced Encryption Standard

(AES) for SNMP

RMON (Stats, History, Alarms, Events,

Filters, Packet Capture)

Secure Copy (SCP)

Secure FTP (SFTP)

Simple Network Management Protocol

(SNMP) v1/v2c/v3

Simple Network Time Protocol (SNTP)

SSHv2

RFC 3164 – The BSD Syslog Protocol

TACACS+ for Management Authentication,

Authorization and Auditing

Web-based Management

Webview via SSL Interface

Switch Model Specifications

	B5G124-24	B5G124-24P2	B5G124-48	B5G124-48P2
Performance				
Throughput Capacity wire-speed Mpps (switch / stack)	35.7 Mpps / 285.7 Mpps	35.7 Mpps / 285.7 Mpps	71.4 Mpps / 571.4 Mpps	71.4 Mpps / 571.4 Mpps
Switching Capacity (switch / stack)	48 Gbps / 384 Gbps	48 Gbps / 384 Gbps	96 Gbps / 768 Gbps	96 Gbps / 768 Gbps
Stacking Capacity (switch / stack)	48 Gbps / 384 Gbps	48 Gbps / 384 Gbps	48 Gbps / 384 Gbps	48 Gbps / 384 Gbps
Aggregate Throughput Capacity (switch / stack)	96 Gbps / 768 Gbps	96 Gbps / 768 Gbps	144 Gbps / 1,152 Gbps	144 Gbps / 1,152 Gbps
PoE Specifications				
802.3af Interoperable	N/A	Yes	N/A	Yes
802.3at Interoperable	N/A	Yes	N/A	Yes
System Power	N/A	375 watts per switch with up to 30 watts per port Per-port switch power monitor: • Enable/disable • Priority safety • Overload & short circuit protection	N/A	375 watts per switch with up to 30 watts per port Per-port switch power monitor: • Enable/disable • Priority safety • Overload & short circuit protection
Physical Specifications				
Dimensions (H x W x D)	H: 4.4 cm (1.73") W: 44.1 cm (17.36") D: 36.85 cm (14.51")	H: 4.4 cm (1.73") W: 44.1 cm (17.36") D: 36.85 cm (14.51")	H: 4.4 cm (1.73") W: 44.1 cm (17.36") D: 36.85 cm (14.51")	H: 4.4 cm (1.73") W: 44.1 cm (17.36") D: 36.85 cm (14.51")
Net Weight	4.92 kg (10.85 lb)	6.10 kg (13.45 lb)	5.31 kg (11.70 lb)	6.49 kg (14.30 lb)
MTBF	394,679 hours	345,093 hours	308,359 hours	260,806 hours
Physical Ports	<ul style="list-style-type: none"> • (24) 10/100/1000 auto-sensing, auto-negotiating MDI/MDI-X RJ45 ports • (4) Combo SFP ports • (2) dedicated stacking ports • (1) DB9 console port • (1) RPS connector 	<ul style="list-style-type: none"> • (24) 10/100/1000 PoE (.af + .at) auto-sensing, auto-negotiating MDI/MDI-X RJ45 ports • (4) Combo SFP ports • (2) dedicated stacking ports • (1) DB9 console port • (1) RPS connector 	<ul style="list-style-type: none"> • (48) 10/100/1000 auto-sensing, auto-negotiating MDI/MDI-X RJ45 ports • (4) Combo SFP ports • (2) dedicated stacking ports • (1) DB9 console port • (1) RPS connector 	<ul style="list-style-type: none"> • (48) 10/100/1000 PoE (.af + .at) auto-sensing, auto-negotiating MDI/MDI-X RJ45 ports • (4) Combo SFP ports • (2) dedicated stacking ports • (1) DB9 console port • (1) RPS connector
Power Requirements				
Normal Input Voltage	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC
Input Frequency	50 – 60 Hz	50 – 60 Hz	50 – 60 Hz	50 – 60 Hz
Input Current	2 A Max	7.5 A Max	2 A Max	7.5 A Max
Power Consumption	63 watts	98 watts	76 watts	156 watts
Temperature				
IEC 6-2-1 Standard Operating Temperature	0° to 50° C (32° to 122° F)	0° to 50° C (32° to 122° F)	0° to 50° C (32° to 122° F)	0° to 50° C (32° to 122° F)
IEC 6-2-14 Non-Operating Temperature	-40° to 70° C (-40° to 158° F)	-40° to 70° C (-40° to 158° F)	-40° to 70° C (-40° to 158° F)	-40° to 70° C (-40° to 158° F)
Heat Dissipation	214 BTUs/Hr	334 BTUs/Hr	258 BTUs/Hr	532 BTUs/Hr
Humidity				
Operating Humidity	5% - 95% non-condensing	5% - 95% non-condensing	5% - 95% non-condensing	5% - 95% non-condensing
Vibration				
	IEC 68-2-6, IEC68-2-36	IEC 68-2-6, IEC68-2-36	IEC 68-2-6, IEC68-2-36	IEC 68-2-6, IEC68-2-36
Shock				
	IEC 68-2-29	IEC 68-2-29	IEC 68-2-29	IEC 68-2-29
Drop				
	IEC 68-2-32	IEC 68-2-32	IEC 68-2-32	IEC 68-2-32
Altitude				
Operating	10,000 ft (3,048 m)	10,000 ft (3,048 m)	10,000 ft (3,048 m)	10,000 ft (3,048 m)
Non-operating	15,000 ft (4,572 m)	15,000 ft (4,572 m)	15,000 ft (4,572 m)	15,000 ft (4,572 m)

Acoustics				
Front of switch (normal operation)	44.5 dB	45 dB	45.5 dB	44.5 dB
Agency and Regulatory Standard Specifications				
Safety	UL 60950-1, CSA 22.1 60950, EN 60950-1, and IEC 60950-1	UL 60950-1, CSA 22.1 60950, EN 60950-1, and IEC 60950-1	UL 60950-1, CSA 22.1 60950, EN 60950-1, and IEC 60950-1	UL 60950-1, CSA 22.1 60950, EN 60950-1, and IEC 60950-1
EMC	FCC Part 15 (Class A), ICES-003 (Class A), BSMI, VCCI V-3, AS/NZS CISPR 22 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, and EN 61000-3-3	FCC Part 15 (Class A), ICES-003 (Class A), BSMI, VCCI V-3, AS/NZS CISPR 22 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, and EN 61000-3-3	FCC Part 15 (Class A), ICES-003 (Class A), BSMI, VCCI V-3, AS/NZS CISPR 22 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, and EN 61000-3-3	FCC Part 15 (Class A), ICES-003 (Class A), BSMI, VCCI V-3, AS/NZS CISPR 22 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, and EN 61000-3-3
B5K125-24		B5K125-24P2		B5K125-48
Performance				
Throughput Capacity wire-speed Mpps (switch / stack)	65.5 Mpps / 523.8 Mpps	65.5 Mpps / 523.8 Mpps	101.2 Mpps / 809.5 Mpps	101.2 Mpps / 809.5 Mpps
Switching Capacity (switch / stack)	88 Gbps / 704 Gbps	88 Gbps / 704 Gbps	136 Gbps / 1,088 Gbps	136 Gbps / 1,088 Gbps
Stacking Capacity (switch / stack)	48 Gbps / 384 Gbps	48 Gbps / 384 Gbps	48 Gbps / 384 Gbps	48 Gbps / 384 Gbps
Aggregate Throughput Capacity (switch / stack)	136 Gbps / 1,088 Gbps	136 Gbps / 1,088 Gbps	184 Gbps / 1,472 Gbps	184 Gbps / 1,472 Gbps
PoE Specifications				
802.3af Interoperable	N/A	Yes	N/A	Yes
802.3at Interoperable	N/A	Yes	N/A	Yes
System Power	N/A	375 watts per switch with up to 30 watts per port Per-port switch power monitor: • Enable/disable • Priority safety • Overload & short circuit protection	N/A	375 watts per switch with up to 30 watts per port Per-port switch power monitor: • Enable/disable • Priority safety • Overload & short circuit protection
Physical Specifications				
Dimensions (H x W x D)	H: 4.4 cm (1.73") W: 44.1 cm (17.36") D: 36.85 cm (14.51")	H: 4.4 cm (1.73") W: 44.1 cm (17.36") D: 36.85 cm (14.51")	H: 4.4 cm (1.73") W: 44.1 cm (17.36") D: 36.85 cm (14.51")	H: 4.4 cm (1.73") W: 44.1 cm (17.36") D: 36.85 cm (14.51")
Net Weight	4.92 kg (10.85 lb)	6.10 kg (13.45 lb)	5.31 kg (11.70 lb)	6.49 kg (14.30 lb)
MTBF	374,029 hours	328,905 hours	297,808 hours	252,940 hours
Physical Ports	<ul style="list-style-type: none"> • (24) 10/100/1000 auto-sensing, auto-negotiating MDI/MDI-X RJ45 ports • (2) Combo SFP ports • (2) 10GE ports • (2) dedicated stacking ports • (1) DB9 console port • (1) RPS connector 	<ul style="list-style-type: none"> • (48)10/100/1000 PoE (.af + .at) auto-sensing, auto-negotiating MDI/MDI-X RJ45 ports • (2) Combo SFP ports • (2) 10GE ports • (2) dedicated stacking ports • (1) DB9 console port • (1) RPS connector 	<ul style="list-style-type: none"> • (48) 10/100/1000 auto-sensing, auto-negotiating MDI/MDI-X RJ45 ports • (2) Combo SFP ports • (2) 10GE ports • (2) dedicated stacking ports • (1) DB9 console port • (1) RPS connector 	<ul style="list-style-type: none"> • (48)10/100/1000 PoE (.af + .at) auto-sensing, auto-negotiating MDI/MDI-X RJ45 ports • (2) Combo SFP ports • (2) 10GE ports • (2) dedicated stacking ports • (1) DB9 console port • (1) RPS connector
Power Requirements				
Normal Input Voltage	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC
Input Frequency	50 – 60 Hz	50 – 60 Hz	50 – 60 Hz	50 – 60 Hz
Input Current	2 A Max	7.5 A Max	2 A Max	7.5 A Max
Power Consumption	59 watts	103 watts	94 watts	162 watts
Temperature				
IEC 6-2-1 Standard Operating Temperature	0° to 50° C (32° to 122° F)	0° to 50° C (32° to 122° F)	0° to 50° C (32° to 122° F)	0° to 50° C (32° to 122° F)
IEC 6-2-14 Non-Operating Temperature	-40° to 70° C (-40° to 158° F)	-40° to 70° C (-40° to 158° F)	-40° to 70° C (-40° to 158° F)	-40° to 70° C (-40° to 158° F)
Heat Dissipation	200 BTUs/Hr	351 BTUs/Hr	321 BTUs/Hr	552 BTUs/Hr
Humidity				
Operating Humidity	5% - 95% non-condensing	5% - 95% non-condensing	5% - 95% non-condensing	5% - 95% non-condensing

	B5K125-24	B5K125-24P2	B5K125-48	B5K125-48P2
Vibration				
	IEC 68-2-6, IEC68-2-36	IEC 68-2-6, IEC68-2-36	IEC 68-2-6, IEC68-2-36	IEC 68-2-6, IEC68-2-36
Shock				
	IEC 68-2-29	IEC 68-2-29	IEC 68-2-29	IEC 68-2-29
Drop				
	IEC 68-2-32	IEC 68-2-32	IEC 68-2-32	IEC 68-2-32
Acoustics				
Front of switch (normal operation)	45.5 dB	45 dB	46 dB	45.5 dB
Altitude				
Operating	10,000 ft (3,048 m)			
Non-operating	15,000 ft (4,572 m)			
Agency and Regulatory Standard Specifications				
Safety	UL 60950-1, CSA 22.1 60950, EN 60950-1, and IEC 60950-1	UL 60950-1, CSA 22.1 60950, EN 60950-1, and IEC 60950-1	UL 60950-1, CSA 22.1 60950, EN 60950-1, and IEC 60950-1	UL 60950-1, CSA 22.1 60950, EN 60950-1, and IEC 60950-1
EMC	FCC Part 15 (Class A), ICES-003 (Class A), BSMI, VCCI V-3, AS/NZS CISPR 22 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, and EN 61000-3-3	FCC Part 15 (Class A), ICES-003 (Class A), BSMI, VCCI V-3, AS/NZS CISPR 22 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, and EN 61000-3-3	FCC Part 15 (Class A), ICES-003 (Class A), BSMI, VCCI V-3, AS/NZS CISPR 22 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, and EN 61000-3-3	FCC Part 15 (Class A), ICES-003 (Class A), BSMI, VCCI V-3, AS/NZS CISPR 22 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, and EN 61000-3-3

Redundant Power Supply Equipment Specifications

STK-RPS-150CHAS2 Power Shelf

Power Supply Slots

2

Dimensions (H x W x D)*

5.5 cm (2.2") x 48.2 cm (19.0") x 18.0 cm (7.0")

Weight

0.95 kg (2.09 lbs)

*Note: dimensions include integrated rack mount ears

STK-RPS-150CHAS8 Power Shelf

Power Supply Slots

8

Dimensions (H x W x D)*

22.26 cm (8.77") x 44.0 cm (17.3") x 26.4 cm (10.4")

Weight

5.27 kg (11.6 lbs)

STK-RPS-150PS Power Supply

Dimensions (H x W x D)

19.6 cm (7.7") x 5.2 cm (2.04") x 25.7 cm (10.1")

Net Weight (Unit Only)

1.75 kg (3.85 lbs)

Gross Weight (Packaged Unit)

3.20 kg (7.04 lbs)

MTBF

300,000 hours

Operating Temperature

0° C to 50° C (32° F to 122° F)

Storage Temperature

-30° C to 73° C (-22° F to 164° F)

Operating Relative Humidity

5% to 95%

AC Input Frequency Range

47 – 63 Hz

AC Input Voltage Range

85 – 264 VAC

Maximum Output Power

156 W continuous

STK-RPS-500PS Power Supply

Dimensions (H x W x D)*

4.45 cm (1.75") x 44.5 cm (17.5") x 16.5 cm (6.5")

Net Weight (Unit Only)

3.47 kg (7.63 lbs)

Gross Weight (Packaged Unit)

4.95 kg (10.89 lbs)

MTBF

589,644 hours at 25° C (77° F)

Operating Temperature

0° C to 50° C (32° F to 122° F)

Storage Temperature

-30° C to 73° C (-22° F to 164° F)

Operating Relative Humidity

5% to 95%

AC Input Frequency Range

47-63 Hz

AC Input Voltage Range

90 - 264 VAC

Maximum Output Power

500 W continuous

Ordering Information

Part Number	Description
B5 Switches	
B5G124-24	(24) 10/100/1000 RJ45 ports, (4) combo SFP ports, (2) 12G stacking ports and external RPS connector. Total active ports per switch: (24) Gigabit ports
B5G124-24P2	(24) 10/100/1000 PoE (.at + .af) RJ45 ports, (4) combo SFP ports, (2) 12G stacking ports and external RPS connector. Total active ports per switch: (24) Gigabit ports
B5G124-48	(48) 10/100/1000 RJ45 ports, (4) combo SFP ports, (2) 12G stacking ports and external RPS connector. Total active ports per switch: (48) Gigabit ports
B5G124-48P2	(48) 10/100/1000 PoE (.at + .af) RJ45 ports, (4) combo SFP ports, (2) 12G stacking ports and external RPS connector. Total active ports per switch: (48) Gigabit ports
B5K125-24	(24) 10/100/1000 RJ45 ports, (2) combo SFP ports, (2) 10GE ports, (2) 12G stacking ports and external RPS connector. Total active ports per switch: (24) Gigabit ports + (2) 10GE ports
B5K125-24P2	(24) 10/100/1000 PoE (.at + .af) RJ45 ports, (2) combo SFP ports, (2) 10GE ports, (2) 12G stacking ports and external RPS connector. Total active ports per switch: (24) Gigabit ports + (2) 10GE ports
B5K125-48	(48) 10/100/1000 RJ45 ports, (2) combo SFP ports, (2) 10GE ports, (2) 12G stacking ports and external RPS connector. Total active ports per switch: (48) Gigabit ports + (2) 10GE ports
B5K125-48P2	(48) 10/100/1000 PoE (.at + .af) RJ45 ports, (2) combo SFP ports, (2) 10GE ports, (2) 12G stacking ports and external RPS connector. Total active ports per switch: (48) Gigabit ports + (2) 10GE ports
Cables	
STK-CAB-SHORT	Stacking cable for connecting adjacent B5/C5 switches (30cm)
STK-CAB-LONG	Stacking cable for connecting top switch to bottom switch in a B5 or C5 stack (1m)
STK-CAB-2M	Stacking cable for B5/C5 models (2m)
STK-CAB-5M	Stacking cable for B5/C5 models (5m)
SSCON-CAB	Spare DB9 Console Cable
Redundant Power Supplies	
STK-RPS-150CH2	2-slot modular power supply shelf (power supply STK-RPS-150PS sold separately)
STK-RPS-150CH8	8-slot modular power supply shelf (power supply STK-RPS-150PS sold separately)
STK-RPS-150PS	150W Non-PoE redundant power supply
STK-RPS-500PS	500W 802.3at PoE redundant power supply

Transceivers

Enterasys transceivers provide connectivity options for Ethernet over twisted pair copper and fiber optic cables with transmission speeds from 100 Megabits per second to 10 Gigabits per second. The Enterasys B5 10GE ports support SFP+ transceivers that operate at 10GE, but do not support 1GE transceivers. All Enterasys transceivers meet the highest quality for extended life cycle and the best possible return on investment. For detailed specifications, compatibility and ordering information please go to <http://www.enterasys.com/products/transceivers-ds.pdf>.

Warranty

As a customer-centric company, Enterasys is committed to providing quality products and solutions. In the event that one of our products fails due to a defect, we have developed a comprehensive warranty that protects you and provides a simple way to get your products repaired or media replaced as soon as possible.

B-Series switches come with the Enterasys lifetime warranty against manufacturing defects. For full warranty terms and conditions please go to: www.enterasys.com/support/warranty.aspx.

Service and Support

Enterasys Networks provides comprehensive service offerings that range from Professional Services to design, deploy and optimize customer networks, customized technical training, to service and support tailored to individual customer needs. Please contact your Enterasys account executive for more information about Enterasys Service and Support.

Contact Us

For more information, call Enterasys Networks toll free at 1-877-801-7082, or +1-978-684-1000 and visit us on the Web at enterasys.com



© 2010 Enterasys Networks, Inc. All rights reserved. Enterasys Networks reserves the right to change specifications without notice. Please contact your representative to confirm current specifications. Please visit <http://www.enterasys.com/company/trademarks.aspx> for trademark information.

