



Officine
Orobiche



data sheet for level switch series 40

doc. N. **P17/4351**

quantity **6**

pos **2** of **3** rev **0**

model **41A.JL.HC.M4.WP.XX**

tag		fluid	Density kg/dm3	temp. °C min/oper/des	press. barg min/oper/des	switch point mm H/L H/L		
s1		LIQUID	1	./20./40	1./1			
s2								
s3								
s4								
s5								
s6								
s7								
s8								
s9								
s10								
01	connections pos.	TOP						
02	connections type	3"ANSI 150 RF 125/250						
03	.	.						
04	body mat.	AISI 316L	26	label		AISI 316		
05	attraction sleev	NICKEL	27					
06	Nipple/Enclus. Tube	AISI 316L	28	body rating		ANSI 150		
07	antisteam	NO	29	hydraulic test (bar)				
08	internal parts	HASTELLOY C	30	.		.		
09	spring	HASTELLOY C	31	.				
10	rope	HASTELLOY C L=1m	32	form		FIG.1		
11	.	.	33	.				
12	float	HASTELLOY C	34	.		.		
13	.	n°1 Ø76X240mm	35	.				
14	.	.	36	.		.		
15	nace	no	37	.				
16	paint	.	38	.		.		
17	.	.	39	.				
18	housing	ALUMINIUM WP IP 66						
19								
20	fins	.						
21	switch groups	n°1 M4 SPDT (24VDC 1 A) RES .						
22	electric connection	1/2" NPTF III .						
23	Tamb min/max	-10 / 45°C			Fig.1  Fig.2  Fig.3 			
24	PED 2014/68/UE	Art. 4.3						
25	AREA	.						
v1								
v2								
v3								
v4								
v5								
n1								
n2								
n3								
n4								
n5								
issued UV.....date							lug-17	