

Description

DUOVENT MVD and MVDR Series, MINIVENT MV and MVR Series, MICROVENT MKV, MKVR, MKL and MKLR Series, FLOATVENT 2161C Series and MAXIVENT MXV Series valves are automatic and/or manual devices for venting air from heating and air conditioning systems.

MVD

DUOVENT (PATENTED)

Automatic and manual air vent valve with unscrewable inspection cover. CW617N brass body and cover. Corrosion-resistant technopolymer float switch. PN 12 bar. Maximum operating pressure: 8 bar. Maximum temperature: 115°C. Automatic discharge capacity at 3 bar: 17.9 NL/min. Manual discharge capacity at 3 bar: 139.5 NL/min. Also suitable for water with additive (glycol up to 30%).



Type	Part No.	DN	Weight (g)
MVD	0250608	1/4"	195
MVD	0250610	3/8"	200
MVD	0250615	1/2"	200

MVDR

DUOVENT

MVD Series air vent valve with **RIA Series** automatic shut-off valve.



Type	Part No.	DN	Weight (g)
MVDR	0250708	1/4"	210
MVDR	0250710	3/8"	220
MVDR	0250715	1/2"	250

MV

MINIVENT

Automatic air vent valve with unscrewable inspection cover. CW617N brass body and cover. Corrosion-resistant polythene float switch. PN: 12 bar. Maximum temperature: 115°C. Also suitable for water with additive (glycol up to 30%).



Type	Part No.	DN	Weight (g)
MV	0250008	1/4"	195
MV	0250010	3/8"	190
MV	0250215	1/2"	200

MVR

MINIVENT

MV Series automatic air vent valve with RIA automatic shut-off valve.



Type	Part No.	DN	Weight (g)
MVR	0250108	1/4"	215
MVR	0250110	3/8"	220
MVR	0250115	1/2"	240

Specification text

MVD Series

Automatic and manual air vent valve DUOVENT **MVD Series** – WATTS brand – with unscrewable inspection cover. CW617N brass body and cover. Corrosion-resistant polythene float switch. PN 12 bar. Max. operating pressure: 8 bar. Max. temperature: 115°C. Automatic discharge capacity at 3 bar: 17.9 NL/min. Manual discharge capacity at 3 bar: 139.5 NL/min. Also suitable for water with additive (glycol up to 30%).

MV Series

Automatic air vent valve MINIVENT **MV Series** – WATTS brand – with unscrewable inspection cover. CW617N brass body and cover. Corrosion-resistant polythene float switch. PN 12 bar. Max. temperature: 115°C. Also suitable for water with additive (glycol up to 30%)

MKV Series

Vertical automatic air vent valve MICROVENT **MKV Series** – WATTS brand. CW617N brass body and cover. Equipped with O-ring. PN 10 bar. Max. temperature: 110°C. Also suitable for water with additive (glycol up to 30%)

MKL Series

Lateral automatic air vent valve MICROVENT **MKL Series** – WATTS brand. CW617N brass body and cover. Equipped with O-ring. PN 10 bar. Max. temperature: 110°C. Also suitable for water with additive (glycol up to 30%)

2161C Series

Vertical automatic air vent valve FLOATVENT **2161C Series** – WATTS brand. CW617N brass body. Equipped with O-ring. Suitable for installation on the head connections of coplanar manifolds. PN 10 bar. Max. temperature: 110°C.

MXV Series

High-flow automatic air vent valve MAXIVENT **MXV Series** – WATTS brand. Equipped with manual vent valve. Cast iron body and cover with epoxy paint finish. PN 12 bar. Max. operating temperature: 115°C. 3/8" F air outlet connection.

The descriptions and photographs contained in this product specification sheet are supplied by way of information only and are not binding.

Watts Industries reserves the right to carry out any technical and design improvements to its products without prior notice. Warranty: All sales and contracts for sale are expressly conditioned on the buyer's assent to Watts terms and conditions found on its website at www.wattsindustries.com. Watts hereby objects to any term, different from or additional to Watts terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Watts.



Watts Industries Italia S.r.l.

Via Brenno, 21 • 20853 Biassono (MB) • Italy

Tel. +39 039 4986.1 • Fax +39 039 4986.222

infowattsitalia@wattswater.com • www.wattsindustries.com