

FEATURES

- Quick installation and connection to systems: filter and regulator functions in a "single unit"
- Light weight and robust design for installation on piping systems

GENERAL

Fluid	Air or inert gas
Maximum inlet pressure (bar) P1 / at 23°C	12
/ at 50°C	10
Adjustable pressure ranges (bar) P2	0,5 to 8
Hysteresis (bar)	0,35
Ambient temperature range (°C)	+0 to +50
Max. flow (Qv at 6,3 bar)	See table below and chart
Regulator	Self-relieving

CONSTRUCTION

Filtering capacity	25 µm (5 µm on request)
Semi-automatic drain	Operating pressure: min. 1,2 bar
Pressure control knob	Locking "pull-turn-push"
Regulating device	With rolling diaphragm (very low hysteresis)



SPECIFICATIONS

pipe size	bowl capacity	adjustable pressure range	flow			gauge diameter	catalogue number	
			inlet pressure P1	Setpoint P2 = 6,3 bar ΔP = 1 bar			semi-automatic drain	
				(bar)	l/min (ANR)		dm³/s (ANR)	with 0-10 bar gauge
(G)	(cm³)	(bar)	(bar)					
25 µm - Polycarbonate bowl WITH protector ⁽¹⁾								
1/8	28	0,5 to 8	8	550	9	40	34225203	34225201
1/4	28	0,5 to 8	8	650	11	40	34225204	34225202
25 µm - Polycarbonate bowl WITHOUT protector								
1/8	28	0,5 to 8	8	550	9	40	34225123	34225121
1/4	28	0,5 to 8	8	650	11	40	34225124	34225122

⁽¹⁾ Adjustment range 0,2 to 3 bar and other values on request.


INSTALLATION

- Systems must be installed with the bowls in vertical position (at the bottom)
- Air flow direction indicated by arrow and "IN" - "OUT" marking on body
- Use an alkaline solution (soapy water) and not a solvent for cleaning the polycarbonate bowls and sight glasses


ACCESSORIES (See Accessories pages)

OPTIONS

• Manual drain, code: 662563			
• Equipment for use in potentially explosive atmospheres caused by dusts or gases (ATEX Directive 2014/34/EU)			
zones	classification	gas group	ATEX option code
2-22	II 3GD c T85°C (T6)	IIA-IIIB-IIC	612077
1-21	II 2GD c IIB T85°C (T6)	IIB	612076

PRESSURE LOSS VERSUS AIR FLOW CURVE

DIMENSIONS (mm), WEIGHT (kg)

Weight: 0,190



- ① Mounting with top bracket (accessory) and mounting ring
 ② Semi-automatic drain, connectable to G1/8 port

- ③ 40 mm dia. pressure gauge