



NO Readme Files

Series NO MC-362

Name: Multi-Function UP/Down Counter

Descripting

Digits-6

## PRODUCT DESCRPTION

Outline	DIN 72×72			
Model	MC-341	MC-342	MC-361	MC-362
Digits	4	4	6	6
Preset	Single	Duet	Single	Duet
Output Method	One	Tow	One	Two
	Relay	Relay	Relay	Relay
Contact Reted	3A/250VAC			
Power Supply	90~265 VAC 50/60 Hz			
Current Consumption	5VA max.			
DC Output	12V/100mA max.			
Input Method	NPN Single Phase or Two Phase Selectable			
Counting Method	Increasing or Decreasing Counting Selectable			
Response Time	0.1ms~999.9 ms Settable			
Output Control	N/R/C/A Selectable			
Output Reset Time	0.01~99.99 Sec Settable			
Multiplier	0.001~9.999 Settable			
Memory Method	EEPROM			
ESD Strength	Over 8KV			
Dielectric Strength	Over 2.5KV/1 min , Between Power and Each Other Terminal			
Isolation Strength	Over 100MΩ/500VDC , Between Power and Each Other Terminal			
Operating Circum.	-20°C ~ +80°C ; 35% ~ 85%RH			
<a href="http://www.photosensor.com.tw">http://www.photosensor.com.tw</a>				