



Pneumatic pump 3:1
SRL 860-200/220-l-container

Item number: 19 235
EAN: 4103810192357
Discount group: D

Technical data

Length of suction tube (mm): 860
 Pressure ratio: 3:1
 Max. diameter (mm): 130
 Max. air pressure (bar): 8
 Min. air pressure (bar): 2
 Recommended air pressure (bar): 6
 Cylinder capacity engine (cm³): 220
 Cylinder capacity pump (cm³): 70
 Quantity of strokes at 8 bar at a free-flow (strokes/min): 260
 Pump capacity at 8 bar at a free-flow (l/min): 22
 Pump pressure at 8 bar air pressure (bar): 24
 Air consumption at 8 bar air pressure (l/min): 470
 Length of discharge pipe work: Depends on size of installation.
 Max. suction height: 6 m, suction tube G 3/4"
 Compressed air connection: G 1/4" female
 Oil connection - suction side: G 3/4" female
 Oil connection - delivery side: G 1/2" male
 Connection container: G 2" male, drum adapter
 Noise level idle running acc. to ISO 9614-2 at a distance of 2 m (db A): 78
 Noise level under load acc. to ISO 9614-2 at a distance of 2 m (db A): 77
 Viscosity of discharged liquid: oil up to SAE 90
 Classical liquids to be discharged: engine, gear and hydraulic oil
 Time duration for 1 complete container draining: 200 l oil in 9 minutes
 Lacquering: blue, Pantone 294 C
 Length of engine (mm): 360
 Weight of motor (kg): 3,800
 Weight (kg): 5,65

Specification

- Pneumatic oil pump 3:1
- For 200/220 l container
- Suction tube, G 3/4" male
- To discharge engine, gear and hydraulic oils
- Ideal for direct connection to pipe lines up to 70 meters. We strongly recommend the use of an overflow valve ((19 648), 16 bar, or (19 506), 20 bar)
- Can be easily combined with several hose reels

Special notes

- Operate pneumatic pump with maintenance unit (20 218 950)

Packaging

Dimensions LxWxH (mm): 1310 x 190 x 195
 Weight (kg): 6,60
 Packing unit: 1,0