PNEUMATIC - 410 eSAFE SERIES



255


255

Single Shut-off

->+->--<

FEATURES	BENEFITS
Extremely high flow capacity Compact design	Fast, easy, one hand operation High performance Strong and durable for long life
SPECIFICATIONS	
Nominal flow diameter	10.4 mm (13/32")
Air flow	4000 I/min (141.2 CFM)
Max. working pressure	16 bar (232 psi)
Min. burst pressure	140 bar (2030 psi)
Temperature range	-20°C to +100°C (-4°F to +212°F)
Coupling material	Zinc plated steel / brass
Nipple material	Hardened zinc plated steel
Connection force	140 N

NPT Threads are available



*Flow capacity measured at 6 bar (87 psi) inlet pressure and pressure drop at 0.5 bar (7 psi)

CARRES

eSAFE VENTED SAFETY COUPLINGS



HOSE CONNECTION



PART NUMBER	CONNECTION
C104102004	10 mm 3/8"
C104102005	13 mm 1/2"
C104102006	16 mm 5/8"
C104102007	19 mm 3/4"







C104102154 3/8" BSPT C104102155 1/2" BSPT C104102157 3/4" BSPT	PART NUMBER	CONNECTION
	C104102154	3/8" BSPT
C104102157 3/4" BSPT	C104102155	1/2" BSPT
	C104102157	3/4" BSPT



CEJN SERIES 410

FEMALE THREAD

PART NUMBER	CONNECTION
C104102204	3/8" BSPP
C104102205	1/2" BSPP
C104102207	3/4" BSPP



CEJN SERIES 410 STREAMLINE CONNECTION

PART NUMBER	CONNECTION	
C104102066	11.0 x 16.0 mm	
C104102068	13.0 x 18.0 mm	

STANDARD NIPPLES

CEJN SERIES 410

HOSE BARB

PART NUMBER	CONNECTION
C104105002	6 mm 1/4"
C104105003	8 mm 5/16"
C104105004	10 mm 3/8"
C104105005	13 mm 1/2"
C104105006	16 mm 5/8"
C104105007	19 mm 3/4"

CEJN SERIES 410 MALE THREAD

with Loctite Dry-Seal®

PART NUMBER	CONNECTION
C104105152	1/4" BSPT
C104105154	3/8" BSPT
C104105155	1/2" BSPT
C104105157	3/4" BSPT

CEJN SERIES 410

FEMALE THREAD

PART NUMBER	CONNECTION
C104105202	1/4" BSPP
C104105204	3/8" BSPP
C104105205	1/2" BSPP
C104105207	3/4" BSPP



CEJN SERIES 410





CEJN SERIES 410 NIPPLE TO BSPT MALE

			A.	13
€ mm €	ins 🖈	€ BAFT	bar	
12.5	1/2	1/2	20	
19.0	3/4	3/4	20	
	12.5	12.5 1/2	12.5 1/2 1/2	12.5 1/2 1/2 20